

Description

METHOD AND APPARATUS FOR PARASITIC LOAD COMPENSATION

Technical Field

- [01] This invention relates generally to systems for monitoring and determining the power output of an engine and, more particularly, to a method and apparatus for more accurately determining the net power output of an engine associated with a work machine or other vehicle by automatically compensating for any parasitic loads encountered during engine operation.

Background

- [02] Engines associated with work machines such as earthmoving and excavating equipment as well as over the road and off-road vehicles not only provide motive force for the particular work machine or other vehicle but such engines also power peripheral devices such as hydraulic pumps, cooling fans, compressors, air conditioners, generators (alternators) and other parasitic load components. Depending upon the particular work machine or other vehicle, the engine may be operated at a substantially constant speed or at variable speeds where instantaneous changes in output power are needed. In a similar fashion, some parasitic loads may require a substantially constant power input such as a cooling fan operating at a particular fan speed regardless of engine speed, whereas other parasitic loads may require a variable power input under certain operating conditions, even at the same engine speed, such as a hydraulic pump providing power to various hydraulic components during a digging or trenching operation.
- [03] Control systems for controlling the operation of an engine are also known and are commonly used on work machines and other vehicles. By sensing

various operating parameters such as engine speed, throttle/fuel injection position, manifold pressure, various temperatures and other engine operating parameters, appropriate output signals can be made to various systems so as to operate the engine more efficiently and optimally depending upon the particular work task being performed. Since an engine controller typically monitors the power generated by the engine and the amount of power being required by various operating components of the work machine or other vehicle, and since this information is typically broadcasted or outputted by the engine controller for use by other systems in optimally controlling a particular work task being performed, it is important that the engine controller accurately broadcast the net power output of the engine including taking into account the power necessary to operate parasitic loads. Since the engine controller does not typically know the nature and level of the parasitic loads being imposed upon the engine during a particular work task, the net power output of the engine broadcasted by the engine controller is deficient; it does not compensate for all parasitic load operation; and it does not yield an accurate determination of the amount of power that the engine must generate at any particular point in time. This inaccuracy is exaggerated with respect to work machines such as large earthmoving and excavating equipment, track type tractors and a wide variety of other types of heavy duty equipment wherein large amounts of power are required to drive certain types of parasitic loads.

[04] Accurately determining the net power output of a particular engine is likewise complicated due to the fact that many manufacturers purchase the basic engine separate and apart from the various parasitic load components which will be added later to the completed work machine or other vehicle. Once the engine, vehicle chassis and all related accessories and components are assembled, the engine is mated with a particular vehicle chassis and all of the accessory drives and other parasitic load components including the transmission and associated drive train are linked and coupled thereto. Since the engine

manufacturers do not know what type of parasitic loads will be associated with a particular engine and, as a result, do not know the particular power requirements associated with such parasitic loads, they cannot program the associated engine controller to compensate for the wide variety of different power requirements associated with the operation of a wide variety of different parasitic loads when determining the net power output of the engine. This mating of the engine with the vehicle chassis and its associated parasitic load components exemplifies the difficulty in accurately compensating for the power requirements associated with any parasitic load encountered during a particular work task.

[05] It is therefore desirable to provide a method and apparatus for more accurately determining the net power output of an engine available for performing a particular work task taking into account and compensating for all parasitic loads encountered during completion of such task. It is also desirable to provide a method and apparatus that will provide real time information indicative of available engine power to ensure that the available net power output of the engine is adequate to accomplish a particular task such as control operation of the engine and/or peripheral devices associated therewith.

[06] Accordingly, the present invention is directed to overcoming one or more of the problems as set forth above.

Summary of the Invention

[07] In one aspect of the present invention, a control system is disclosed for determining the net power output of an engine associated with a work machine or other vehicle wherein the work machine or other vehicle includes an engine operable to provide power to at least two power-operated components, at least one of the power-operated components being a parasitic load component. The present control system includes an electronic controller coupled to the engine, at least one sensor coupled to the controller for inputting at least one signal representative of certain operating conditions of the engine, and at least one other sensor coupled to the controller for inputting at least one signal

representative of the operation of the at least one parasitic load component. Stored within the memory of the controller is data relating to the power requirements of the at least one parasitic load component when that component is in operation at a plurality of different engine operating conditions or engine speeds. The controller is operable to determine the total output power of the engine based upon at least one of the sensor input signals; it is operable to determine the power requirements of the at least one parasitic load component based upon at least one of the sensor input signals; and it is operable to provide an output signal representative of the difference between the total output power of the engine and the power requirements associated with the at least one parasitic load component. This output signal can be used to control various operations of the work machine or other vehicle.

[08]

In another aspect of the present invention, a method is disclosed for determining the net power output of an engine associated with a work machine or other vehicle wherein the work machine or other vehicle includes an engine operable to provide power to at least two power-operated components, at least one of the power-operated components being a parasitic load component. The present method includes coupling an electronic controller to the engine, sensing at least one engine parameter representative of the operating condition of the engine, determining the total output power of the engine based upon the at least one sensed engine parameter, sensing whether the at least one parasitic load component is in operation during operation of the engine, and determining the power requirement associated with the operation of the at least one parasitic load component. Based upon the power requirements associated with the parasitic load components in operation, the present method further determines the difference between the total output power of the engine and the power requirements associated with all parasitic load components in operation and outputs a signal representative of this difference.

Brief Description of the Drawings

- [09] For a better understanding of the present invention, reference may be made to the accompanying drawings in which:
- [10] Fig. 1 is a simplified side elevational view of one embodiment of a truck chassis.
- [11] Fig. 2 is a schematic diagram of an engine control system constructed in accordance with the teachings of one embodiment of the present invention.
- [12] Fig. 3 is a simplified side elevational view of a work machine in the form of an excavator.
- [13] Fig. 4 is a flow chart of the operating steps for an engine control system constructed in accordance with the teachings of one embodiment of the present invention.
- [14] Fig. 5 is a flow chart of the operating steps for an engine control system constructed in accordance with the teachings of another embodiment of the present invention.

Detailed Description

- [15] Referring to Fig. 1, numeral 10 in Fig. 1 represents a typical truck chassis having an engine 12 associated therewith including some typical peripheral devices or parasitic load components such as, for example, an air conditioning compressor 14, an alternator 16, a hydraulic pump 18, and a cooling fan 20. As illustrated in Fig. 1, the engine 12 associated with the particular truck chassis 10 is used to drive such vehicle as well as the other systems associated therewith including still other parasitic load components. In this regard, it is recognized that a typical vehicle manufacturer will collect and gather all of the necessary components associated with the construction and operation of a particular vehicle or work machine such as the chassis 10, engine 12, and parasitic load devices 14-20 illustrated in Fig. 1 and thereafter assemble the same

onto the vehicle chassis during the construction and assembly process. It is also recognized and anticipated that the various parasitic load components will vary depending upon the particular vehicle or work machine involved. In a typical application there are some parasitic loads that can be engaged by the engine controller and others that are active when the engine is operating (such as power steering pumps, air compressors and the like). Once the engine and its associated parasitic load systems or components are married to the vehicle chassis, a calibration process is performed wherein each parasitic load component is engaged under predetermined engine operating conditions or is assumed to be active (in the case of these parasitic loads that are not capable of individual activation), and the parasitic loads or power requirements associated with each of those parasitic load components is determined and stored for future use as will be hereinafter explained. This calibration process is repeated under the various predetermined engine operating conditions and the amount of power required to operate each parasitic load under each of the various operating conditions tested is individually determined. This would include operating each parasitic load at a plurality of different engine speeds. A database of the parasitic load power requirement values thus obtained is then stored in the memory of the engine controller for future use.

- [16] Number 22 in Fig. 2 represents one embodiment of an engine control system that incorporates the principles of the present invention. Because of the varying parasitic load configuration associated with any particular work machine or other vehicle, the engine control system 22 illustrated in Fig. 2 is merely representative of one of many systems incorporating the principals of the present invention and which can be utilized to more accurately determine the net power output of an engine during the operation thereof. As illustrated in Fig. 2, engine control system 22 includes an engine speed sensor 24, a throttle or fuel injection position sensor 26, a hydraulic pump pressure sensor 28 and an air conditioning compressor pressure sensor 30, all of which sensors provide input

signals to an electronic control module (ECM) 32. Based upon the signals from sensors 24, 26, 28 and 30, ECM 32 will monitor and determine the net output power of engine 12 and provide appropriate output signals indicative thereof to various systems associated with the vehicle or work machine such as signals 44 and 66 to such systems as a fuel injection control system or engine governor system 68, or to a transmission controller 46 for reasons which will be hereinafter explained.

[17] Electronic engine controllers or modules such as ECM 32 are commonly used in association with work machines and other vehicles for controlling and accomplishing various functions and tasks including monitoring and controlling engine functions such as engine speed, engine load and fuel flow to the respective cylinders and fuel injectors associated with a particular engine. ECM 32 may typically include processing means, such as a microcontroller or microprocessor, associated electronic circuitry such as input/output circuitry, analog circuits or programmed logic arrays, as well as associated memory such as the memory 42 illustrated in Fig. 2. It is known in the art to incorporate within ECM 32 appropriate driver circuitry for delivering current signals to the various valves and other devices associated with various systems on the vehicle or work machine.

[18] An engine speed sensor 24 is coupled to ECM 32 via conductive path 34 for constantly delivering engine speed indicative signals to ECM 32 during the operation of the particular vehicle or work machine. The sensor 24 may be connected to the output shaft of a torque converter, or such sensor may be associated with the cam shaft of engine 12. Engine speed sensors or transducers are well known in the art and are commonly used to measure the engine output speed. Other suitable engine speed sensors such as Hall effect sensors, tachometers and the like may likewise be utilized without departing from the spirit and scope of the present invention.

[19] A throttle/fuel injection position sensor 26 is also coupled to ECM 32 via conductive path 36 for constantly monitoring the engine throttle position and for delivering throttle/fuel injection position indicative signals to ECM 32 during the operation of the particular vehicle or work machine. Such throttle position/fuel injection type sensors are likewise well known in the art, a detailed description of such sensors is not included herein.

[20] In similar fashion, pressure sensors 28 and 30 are likewise coupled to ECM 32 via conductive paths 38 and 40 for monitoring and sensing the pressure of the fluid within the particular system such as the output pressure from a particular hydraulic pump or the outlet pressure associated with a particular air conditioning compressor. Here again, such sensors are well known in the art and a detailed description is not included herein. As will be hereinafter explained, sensors 24 and 26 will be utilized by ECM 32 in order to determine the output power associated with the engine 12 whereas sensors 28 and 30 will be utilized during the calibration process to determine the particular parasitic load or power requirements associated with each parasitic load as well as during the operation of the particular work machine or other vehicle to determine the operation of the particular parasitic load during the operation of the engine.

[21] Within the memory 42 of ECM 32 can be stored various lookup tables, torque converter speed correlation maps, algorithms, and other data which will correlate and/or determine the instantaneous power output of the engine 12 based upon input signals from sensors 24 and 26 as well as the calibration data associated with the operation of each parasitic load as will be hereinafter explained. These maps and calibration information will correlate the relationship between engine operating conditions and total engine output power and will yield net engine power output taking into account the power requirements associated with the operation of any one or more of the parasitic loads associated with a particular vehicle or work machine.

[22] With the parasitic loads attached to the engine 12 and the chassis 10, and no other loads being driven, the engine 12 is operated and allowed to warm up to its operating temperature. The ECM 42 first calibrates the fuel delivery for parasitic loads that are normally active whenever the engine is operating. The ECM 42 preferably accomplishes this by determining the fuel command required to run the engine at predetermined engine speeds and then storing those values as the no-load fuel requirements. Those no-load fuel requirements may then be used to calculate fuel delivery commands when the engine is operating under a working load. Additionally, the ECM 42 may also calibrate power requirements for parasitic loads that can be turned on and off by the controller. To do this, the ECM 42 will preferably operate each parasitic load component while the engine is running at a predetermined engine speed or other predetermined operating condition and the sensors associated with such parasitic load such as sensors 28 and 30 will input signals to ECM 42 indicative of the power requirements associated with operating such parasitic loads at such predetermined engine operating condition. These data will then be stored within memory 42 and the calibration process will be repeated for the same parasitic load under varying operating conditions such as stepping the engine through a plurality of different engine speeds, for example, at increments of 100 rpm. All of this data will then be stored within memory 42 for use during actual vehicle or work machine operation.

[23] With the engine operating, each of the various parasitic loads will be operated in turn to determine its individual power requirements in its on/off condition or, if a variable power requirement is associated with the particular parasitic load, as such parasitic load varies from its minimum to its maximum operating condition at each predetermined operating condition. For example, in the case of a constant speed cooling fan, the power requirements for the fan will be monitored and stored at each of its various operating speeds at each selected engine operating speed. In the case of a hydraulic pump which may operate at

varying power requirements at a selected engine speed, the power requirements for that pump will be monitored and stored as a function of a particular operating condition, for example, the pressure output sensed by sensor 28, between its minimums and maximum load condition, at each selected engine speed. This data can then be used to correlate the sensed operating condition such as pump pressure to the power varying requirements of the parasitic load at each selected engine speed. These load requirements will then be stored or programmed into ECM 32 and sensors such as sensors 28 and 30 will input to ECM 32 the sensed operating condition permitting ECM 32 to know the power requirements in real time for the particular parasitic load being utilized. ECM 32 will then sum all of the parasitic loads in operation at a particular point in time and compare such parasitic load power requirements to the power requirements associated with sensors 24 and 26 to determine the net power output of the engine 12. This output signal, for example, would be indicative of total engine horsepower minus parasitic load horsepower so as to ensure that the remaining available horsepower is adequate to accomplish a particular work task such as performing a particular work task and/or controlling the operation of the engine and/or peripheral devices.

- [24] Once the above-described calibration process is completed and the values associated with the power requirements of the various parasitic loads are determined and stored in memory 42 of ECM 32, ECM 32, via appropriate sensors such as sensors 28 and 30, will determine which particular parasitic loads are operating during a particular operating condition of the vehicle or work machine, it will retrieve their corresponding power requirement values from memory 42 as described above, and it will add those values to determine the total parasitic load upon the engine 12 under that particular operating conditions. This determined parasitic load value can then be taken into account for more accurately determining both the amount of power being currently required from the engine 12 as well as the net power output of the engine available for

performing work. These parasitic load values can be programmed into lookup tables, maps or other algorithms which then provide the proper power requirement relationship between inputs from appropriate sensors such as sensors 28 and 30 and the power usage associated with operation of the particular parasitic load at a particular engine operating condition. ECM 32 can then output or broadcast an appropriate signal indicative of the net power output of the engine available for doing work. This output signal such as signal 44 can then be utilized in controlling, for example, the operation of other systems associated with the particular vehicle or work machine such as the transmission controller 46 illustrated in Fig. 2 which determines when the transmission shifts from one gear to another gear to improve the overall operation of the engine 12 as will be hereinafter explained.

- [25] Referring again to Fig. 1, the truck chassis 10 likewise includes a transmission 48 which is coupled between engine 12 and a differential 50 for driving a pair of wheels 52 when operating a vehicle such as an over the road or off-road truck. It is desirable to control the operation of the transmission 48 such that shifts are made at the right rotational speed of the engine 12, which shifting strategy is determined by the available power output of the engine at a predetermined operating condition. The present control system 22 can be utilized to more accurately determine the proper shifting ranges of an automatic transmission such as the transmission 48 during normal operation by outputting signal 44 to an appropriate transmission controller 46 to accomplish this task. In this regard, ECM 32 can be further programmed with appropriate transmission operating characteristics which will indicate what power output range is needed in order to effect a shift from one gear to the next gear. This adequacy of power can be programmed for each successive pair of gears, or such relationship may be assumed to be uniform for each gear shift. Based upon this stored gear shift information and output signal 44 which is representative of the net power output of the engine 12, ECM 32 will output appropriate signals such as signal 44 to

transmission control 46 to effect a gear shift change. In the case of controlling the shifting of an automatic transmission, signal 44 may be utilized to automatically control the shifting of transmission 48 when an adequate power output level is available as predetermined and preprogrammed into ECM 32. In the event that the particular work machine or other vehicle utilizes a manual transmission, output signal 44 could be utilized to provide an indication to the operator in the cab, such as by an audible and/or visual signal, that the transmission may be shifted manually to the next gear. Other variables affecting the shifting of the transmission may also be taken into account such as surface slope and the weight and load capacity of the work machine or other vehicle. Gear shift available power requirement information can be provided in appropriate maps, lookup tables and the like that could be stored in memory 42. Similarly, if ECM 32 is being used to control a particular vehicle or work machine so as to ensure adequacy of power output for powering the parasitic loads or performing a particular work task, similar programming can likewise be provided.

- [26] Although one embodiment of the present invention as discussed above is directed to using the output signal 44 from ECM 32 to provide a signal indicative of available power to indicate adequate power to control the operation of a transmission 48 associated with a particular vehicle 10, it is also contemplated that the present control system can likewise be utilized to control the operation of the engine 12 itself, or other systems associated with a particular vehicle or work machine. For example, Fig. 3 represents a typical work machine 54 such as a track-type excavator having a pair of tracks 56, an engine 12 for providing motive power for moving the work machine 54 as well as for driving the various parasitic loads associated therewith such as an air conditioning compressor 14, an alternator 16, a hydraulic pump 18, and a cooling fan 20. The cooling fan can operate in a continuous mode, an on/off mode, or it can be a variable speed fan having a variable power requirement, all depending upon the

cooling needs of the engine 12. Although other parasitic loads are associated with the work machine 54, the parasitic loads 14, 16, 18 and 20 are specifically identified for illustrative purposes only. During operation of the bucket 58, the hydraulic pump 18 is used to pressurize hydraulic fluid to operate the various components associated with the bucket 58 which typically includes a plurality of hydraulic cylinders 60, a boom 62 and a stick 64. Such constructions are well known in the art and need not be described in further detail herein. Once the work machine 54 is positioned at its desired location by having the engine 12 drive the tracks 56 in a known manner, the work machine 54 is stopped at the desired location and the transmission (not shown) is placed in neutral. The engine 12 is then allowed to continue to run so as to power the hydraulic pump 18 and the other parasitic loads associated therewith. Movement of the bucket 58 via the boom and stick members 62 and 64 to properly orient the same for a digging operation will require considerably less hydraulic pressure or power output from engine 12 as compared to when the bucket 58 is engaged with the earth and additional hydraulic pressure which translates into additional power output from the engine is required in order to commence the digging operation.

[27] In the particular application identified above with respect to work machine 54, ECM 32 would receive input signals from sensors 24, 26, 28 and possibly 30 indicative of the total power output of the engine 12 as well as the power requirements associated with the parasitic loads represented by sensors 28 and 30. Based upon the calibration data stored in memory 42 representing the particular power requirements associated with the parasitic loads being sensed by sensors 28 and 30, a signal 44 is again generated and outputted by ECM 32 indicative of the difference between the total power output of engine 12 and the parasitic load power requirements, that is, the available remaining net power output of engine 12. In this particular scenario, ECM 32 can determine if this available power output is adequate according to preprogrammed criteria to power the parasitic loads in order to accomplish the particular work task. If the

available power is not adequate, ECM 32 can affect an increase in power output of the engine 12 such as by outputting a signal 66 to an appropriate system such as a fuel injector control system or engine governor 68 until an adequate level of power is available. As the signals 38 and 40 from sensors 28 and 30 change indicating a change in the power requirements associated with such parasitic loads, ECM 32 will automatically and in real time process such signals and control the operation of engine 12 in order to ensure that the necessary power and other engine operating conditions are maintained in order to accomplish the particular work task. Although input signals 34, 36, 38 and 40 are received and processed preferably contemporaneously with the actual work operation, it is recognized and anticipated that delays may be built into the processing of the input signals as well as the generation of the new output signals if so desired, such as outputting signal 66 to the fuel injector control system or engine governor 68.

- [28] Calibration and programming of ECM 32 can be accomplished through the use of a remote device such as a service tool operated by a technician, or through the use of an on-board computer associated with the particular vehicle or work machine. It is also recognized and anticipated that ECM 32 may be a learning ECM which can be programmed to automatically update the power requirements of the various parasitic loads from time-to-time by either periodically re-running the calibration process for each parasitic load, either manually or automatically, or by automatically updating the calibration data stored in memory 42 during actual vehicle or work machine operation when individual parasitic loads can be isolated at particular engine operating conditions. In addition, if a parasitic load component is changed, for example, the hydraulic pump is replaced, ECM 32 would either manually or automatically generate new calibration data representative of the power requirements associated with the new parasitic load component as previously explained.

Industrial Applicability

[29] As described herein, the present engine control system has particular utility in a wide variety of different types of work machines, other equipment or vehicles and provides for improved operating efficiency and engine performance by compensating for the power requirements associated with the parasitic loads in operation during a particular work task. Parasitic loads are sensed during engine operation, the engine power requirements associated with each operating parasitic load are determined and subtracted from the total power output of the engine, and a signal indicative of the net output power of the engine is broadcasted or outputted for use in more efficiently controlling the operation of the engine as well as other systems associated with the work machine or other vehicle. The output signal generated indicates the remaining power output available by the engine for performing other tasks and/or for maintaining the operation of various parasitic loads and other systems. For example, in the case of a truck or other like vehicle, the adequacy of the remaining power output can be determined and correlated to the power needed to effect, for example, operation of peripheral equipment such as a transmission controller to control the proper shifting thereof. In the case of work machines such as earthmoving equipment, mining equipment and other heavy load capacity type equipment, it is desirable to more accurately determine the net power output of the engine over and above the operation of any parasitic loads since the engine is being utilized to perform certain work tasks such as controlling the operation of bucket 58 associated with work machine 54.

[30] Input signals from sensors 24 and 26 are utilized by ECM 32 in a conventional manner for determining the total output power of the engine 12 and for controlling the operation thereof such as via output signal 66 to a fuel injection control system or an engine governor system 68. Output signals such as signal 66 to fuel control type systems are typically directed to various fuel emission valves, fuel injectors and other devices for controlling the delivery of

fuel to the engine, which valves, fuel injectors and other devices are used in a conventional manner. In this regard, ECM 32 would deliver current control signals to such devices in a manner well known to a person skilled in the art.

[31] Input signals from sensors associated with various parasitic loads such as sensors 28 and 30 are likewise utilized by ECM 32 in order to determine which parasitic loads are in operation and, if a variable load, based upon calibration data stored in memory 42, at what operating conditions the variable parasitic load is presently operating at. Based upon the calibration data stored in memory 42, ECM 32 can then determine the output power requirements associated with each operating parasitic load. All of the parasitic load requirements are then summed and thereafter subtracted from the total power output of the engine determined from, for example, input signals 34 and 36, so as to provide a signal that is representative of the total net power output of the engine. This output signal is processed to determine if the level of the difference between the total power output of the engine and the parasitic load requirements are adequate for the operation of the particular vehicle or work machine based upon the particular work task at hand. Appropriate maps, lookup tables, algorithms and the like can be stored in memory 42 or otherwise programmed into ECM 32 in order to measure, determine and compare the power output requirements of the engine and the various parasitic loads in accordance with the teachings of the present invention so as to give a more accurate indication of net engine output power. It is also recognized and anticipated that output signal 44 could be forwarded to some type of monitoring or display system wherein the net power output of the engine would be displayed in the operator cab for use by the operator in controlling the operation of the particular work machine or other vehicle.

[32] An example of alternative embodiments of calibration processes in which the engine ECM 32 measures and stores power level requirements of the various parasitic loads is shown in Figures 4 and 5.

- [33] Referring first to Figure 4, one embodiment is shown. In block 400, program control begins and passes to block 410.
- [34] In block 410, the ECM 32 determines the current power output of the engine, preferably as a function of the amount of fuel being injected into the engine and the engine speed. This step preferably involves calibration of no-load fuel injection maps. As noted above, certain parasitic loads may be associated with the engine which cannot be individually turned on and off, and those loads may consume an amount of power that is different than expected. Thus, to account for those differences or for additional or different parasitic loads, a preferred embodiment of the present invention will first calibrate the engine fuel requirement under a no-load condition (i.e., when the engine is not performing any work other than driving the parasitic loads). These measured no-load fuel requirements may be different than those originally stored in memory of the ECM 42 when the engine was manufactured and are then used by the ECM 42 to modify, where appropriate, the actual no-load fuel requirements. In this manner, a preferable embodiment of the present invention will calibrate no-load fuel requirements taking into consideration parasitic loads that are associated with the engine and that cannot be turned on and off. Program control then passes to block 420.
- [35] In block 420 the ECM 32 selects one of the various parasitic load devices for operation. Program control then passes to block 430. In block 430 the ECM 32 activates the selected parasitic load device at a commanded level. Program control then passes to block 440.
- [36] In block 440, the ECM 32 determines the engine power output of the engine with the parasitic load device activated at the particular load level. Program control then passes to block 450.
- [37] In block 450, the ECM 32 calculates the parasitic load device power requirement at that operating level. Preferably, this calculation is made as

a function of the engine power output of block 410 and the engine power output (PPO) of block 440. Program control then passes to block 460.

[38] In block 460, the ECM 32 preferably stores the power required by the parasitic load device for that commanded level of activity in memory 42. Program control passes from block 460 and may return to block 420 in the case where a different parasitic load device is to be selected for calibration or to block 430 in the case where the same parasitic load device is to be calibrated at another activation level. Otherwise, program control passes to block 470 in the case where the calibration routine has finished and program control terminates and returns to the calling program.

[39] In the manner depicted by the program of Figure 4, an ECM 32 can determine and store the power requirements of one or a plurality of parasitic load devices and also determine the parasitic load device's power requirements at one or a plurality of different operating levels.

[40] Referring now to Figure 5, another embodiment of program control that may be used with an embodiment of the present invention is shown. Program control begins in block 500 and passes to block 510.

[41] In block 510, the ECM 32 determines whether the engine is operating at one of a plurality of predetermined engine speeds which in a preferred embodiment is designated as High Idle or Low Idle condition. In a preferred embodiment, the ECM makes the determination of whether the engine is operating at High Idle or Low Idle as a function of the sensed engine speed being within a predetermined tolerance of a desired High Idle Speed or a desired Low Idle Speed, and the engine operating without external load. Typically the ECM 32 may determine that the engine is operating under no external load by monitoring the vehicle speed and determining whether any work implements (if any) are performing work. If the ECM 32 determines that the engine is not operating at a High Idle or a Low Idle condition then program control passes to

block 550. Otherwise, if the ECM 32 determines that the engine is operating in a High Idle or Low Idle Condition, then program control passes to block 520.

[42] In block 520, the ECM 32 determines the fuel command associated with causing the engine to operate at High Idle or Low Idle. Program control then passes to block 530.

[43] In block 530, the ECM 32 preferably compares the fuel delivery command required for the engine to maintain the High/Low Idle Speed to a fuel command required to maintain that speed when there are no parasitic loads. Those skilled in the art will appreciate that if the actual fuel delivery command is greater than the no load value, the additional power (i.e., the amount of power generated by the incrementally greater amount of fuel) is the power required by the parasitic load devices. If the fuel command is equal to the corresponding fuel command stored in memory 42 for the High Idle Fuel Command or Low Idle Fuel Command (depending upon whether the engine state under evaluation is in a High Idle Condition or a Low Idle Condition) then program control passes to block 550, otherwise program control passes to block 540.

[44] In block 540, the ECM 32 adjusts the value of the High Load Fuel Command or the Low Load Fuel Command, as the case may be, as a function of the actual Fuel delivery command. By storing the fuel delivery command as one of the High Load and/or Low Load Fuel Commands and subsequently using that value to calculate fuel commands under actual engine operating conditions, this embodiment of the present invention is able to measure the amount of power required by the parasitic load devices at the High and Low Idle operating points and can then calculate an approximate parasitic load requirement at other points in the engine operating range and use that calculation to make modifications to subsequent fuel delivery commands. Program control then passes from block 540 to block 550 and returns to the calling routine.

[45] In an embodiment of the present invention, the ECM 32 will cause a program illustrated by the flowchart of Figure 5 to be executed when the engine

speed is within a predetermined tolerance of a selected High Idle Speed or Low Idle Speed and the ECM 32 determines that the engine is not operating an external load. In this manner, the ECM 32 automatically determines the parasitic load requirements while the equipment or vehicle is in operation. In alternative embodiments, a calibration mode may be used to force the engine to run at a High Idle Speed and a Low Idle Speed to thereby measure the fuel delivery requirement. Still other embodiments might use a manual mode to cause the engine to run at High Idle and Low Idle and record fuel delivery requirements.

[46] It is also recognized that variations to the operating steps depicted in flow charts of Figure 4 or 5 could be made without departing from the spirit and scope of the present invention. In particular, steps could be added or some steps could be eliminated and such inventions may nevertheless fall within the scope of the present invention.

[47] It is also recognized and anticipated that the calibration process disclosed herein could be activated through the use of an internal or external device associated with the work machine or other vehicle such as through the use of an on-board computer, or such calibration process could be activated through the use of a service tool such as a laptop computer. In either scenario, the calibration process could be activated either manually or automatically on a periodic basis to update ECM 32 with the appropriate parasitic load power requirements. The calibration process could be stored within the on-board computer of the particular work machine or other vehicle, or such program could be stored within the laptop computer and such computer could interface with ECM 32 to activate and run the calibration process.

[48] As is evident from the foregoing description, certain aspects of the present invention are not limited by the particular details of the examples illustrated herein and it is therefore contemplated that other modifications and applications, or equivalence thereof, will occur to those skilled in the art. It is

accordingly intended that the claims shall cover all such modifications and applications that do not depart from the spirit and scope of the present invention.

[49] Other aspects, objects and advantages of the present invention can be obtained from a study of the drawings, the disclosure and the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2